

Page 1 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.05.2024 / 0004
Replacing version dated / version: 10.02.2023 / 0003
Valid from: 28.05.2024
PDF print date: 28.05.2024
Prüfgas 918/5

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

SECTION 1: Identification of the substance/mixture and of the company/undertaking

1.1 Product identifier

Prüfgas 918/5

1.2 Relevant identified uses of the substance or mixture and uses advised against

Relevant identified uses of the substance or mixture:

Test gas

Uses advised against:

No information available at present.

1.3 Details of the supplier of the safety data sheet

Hekatron Vertriebs GmbH
Brühlmatten 9
D-79295 Sulzburg
Tel.: +49 7634 500-0
Homepage: hekatron-brandschutz.de

Qualified person's e-mail address: info@chemical-check.de, k.schnurbusch@chemical-check.de Please DO NOT use for requesting Safety Data Sheets.

1.4 Emergency telephone number

Emergency information services / official advisory body:

Ⓒ

Emergency poisoning centre D-79110 Freiburg Tel.: +49 (0) 761 19240 (24 hour)

Telephone number of the company in case of emergencies:

SECTION 2: Hazards identification

2.1 Classification of the substance or mixture

Classification according to Regulation (EC) 1272/2008 (CLP)

| Hazard class | Hazard category | Hazard statement |
|--------------|-----------------|--|
| Aerosol | 1 | H222-Extremely flammable aerosol. |
| Aerosol | 1 | H229-Pressurised container: May burst if heated. |

2.2 Label elements

Labeling according to Regulation (EC) 1272/2008 (CLP)



Danger

H222-Extremely flammable aerosol. H229-Pressurised container: May burst if heated.

P210-Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking. P211-Do not spray on an open flame or other ignition source. P251-Do not pierce or burn, even after use.
P410+P412-Protect from sunlight. Do not expose to temperatures exceeding 50 °C.

Without adequate ventilation, formation of explosive mixtures may be possible.

2.3 Other hazards

The mixture does not contain any vPvB substance (vPvB = very persistent, very bioaccumulative) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any PBT substance (PBT = persistent, bioaccumulative, toxic) or is not included under XIII of the regulation (EC) 1907/2006 (< 0,1 %).

The mixture does not contain any substance with endocrine disrupting properties (< 0,1 %).

SECTION 3: Composition/information on ingredients

Aerosol

3.1 Substances

n.a.

3.2 Mixtures

| Propan-2-ol | |
|--|---|
| Registration number (REACH) | 01-2119457558-25-XXXX |
| Index | 603-117-00-0 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 200-661-7 |
| CAS | 67-63-0 |
| content % | 1-<5 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |

| Ethyl acetate | |
|--|---|
| Registration number (REACH) | 01-2119475103-46-XXXX |
| Index | 607-022-00-5 |
| EINECS, ELINCS, NLP, REACH-IT List-No. | 205-500-4 |
| CAS | 141-78-6 |
| content % | 1-<5 |
| Classification according to Regulation (EC) 1272/2008 (CLP), M-factors | EUH066 Flam. Liq. 2, H225 Eye Irrit. 2, H319 STOT SE 3, H336 |

For the text of the H-phrases and classification codes (GHS/CLP), see Section 16.
The substances named in this section are given with their actual, appropriate classification!

Page 3 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.05.2024 / 0004

Replacing version dated / version: 10.02.2023 / 0003

Valid from: 28.05.2024

PDF print date: 28.05.2024

Prüfgas 918/5

For substances that are listed in appendix VI, table 3.1 of the regulation (EC) no. 1272/2008 (CLP regulation) this means that all notes that may be given here for the named classification have been taken into account.

The addition of the highest concentrations listed here can result in a classification. Only when this classification is listed in Section 2 does it apply. In all other cases the total concentration is below the classification.

SECTION 4: First aid measures

4.1 Description of first aid measures

First-aiders should ensure they are protected!

Never pour anything into the mouth of an unconscious person!

Inhalation

Remove person from danger area.

Supply person with fresh air and consult doctor according to symptoms.

If the person is unconscious, place in a stable side position and consult a doctor.

Skin contact

Remove polluted, soaked clothing immediately, wash thoroughly with plenty of water and soap, in case of irritation of the skin (flare), consult a doctor.

Eye contact

Remove contact lenses.

Wash thoroughly for several minutes using copious water. Seek medical help if necessary.

Ingestion

Typically no exposure pathway.

Rinse the mouth thoroughly with water.

Do not induce vomiting - give copious water to drink. Consult doctor immediately.

4.2 Most important symptoms and effects, both acute and delayed

If applicable delayed symptoms and effects can be found in section 11 and the absorption route in section 4.1.

In certain cases, the symptoms of poisoning may only appear after an extended period / after several hours.

The following may occur:

Irritation of the respiratory tract

Coughing

Headaches

Dizziness

4.3 Indication of any immediate medical attention and special treatment needed

Symptomatic treatment.

SECTION 5: Firefighting measures

5.1 Extinguishing media

Suitable extinguishing media

Water jet spray / alcohol resistant foam / CO₂ / dry extinguisher.

Unsuitable extinguishing media

High volume water jet

5.2 Special hazards arising from the substance or mixture

In case of fire the following can develop:

Oxides of carbon

Toxic gases

Danger of bursting (explosion) when heated

Possible build up of explosive/highly flammable vapour/air mixture.

5.3 Advice for firefighters

For personal protective equipment see Section 8.

In case of fire and/or explosion do not breathe fumes.

Protective respirator with independent air supply.

According to size of fire

Full protection, if necessary.

Cool container at risk with water.

Dispose of contaminated extinction water according to official regulations.

SECTION 6: Accidental release measures

6.1 Personal precautions, protective equipment and emergency procedures

6.1.1 For non-emergency personnel

In case of spillage or accidental release, wear personal protective equipment as specified in section 8 to prevent contamination. Ensure sufficient ventilation, remove sources of ignition. Avoid dust formation with solid or powder products. Leave the danger zone if possible, use existing emergency plans if necessary. Remove possible causes of ignition - do not smoke. Ensure sufficient supply of air. Avoid contact with eyes or skin. If applicable, caution - risk of slipping.

6.1.2 For emergency responders

See section 8 for suitable protective equipment and material specifications.

6.2 Environmental precautions

Prevent penetration into drains, cellars, working pits or other places in which accumulation could be hazardous. Prevent surface and ground-water infiltration, as well as ground penetration. If accidental entry into drainage system occurs, inform responsible authorities.

6.3 Methods and material for containment and cleaning up

If spray or gas escapes, ensure ample fresh air is available. Without adequate ventilation, formation of explosive mixtures may be possible. Active substance:

Soak up with absorbent material (e.g. universal binding agent, sand, diatomaceous earth) and dispose of according to Section 13.

6.4 Reference to other sections

For personal protective equipment see Section 8 and for disposal instructions see Section 13.

SECTION 7: Handling and storage

In addition to information given in this section, relevant information can also be found in section 8 and 6.1.

7.1 Precautions for safe handling

7.1.1 General recommendations

Ensure good ventilation. Avoid inhalation of the vapours. Avoid contact with eyes or skin. Keep away from sources of ignition - Do not smoke. Take measures against electrostatic charging, if appropriate. Do not use on hot surfaces. Eating, drinking, smoking, as well as food-storage, is prohibited in work-room. Observe directions on label and instructions for use. Use working methods according to operating instructions.

7.1.2 Notes on general hygiene measures at the workplace

General hygiene measures for the handling of chemicals are applicable. Wash hands before breaks and at end of work. Keep away from food, drink and animal feedingstuffs. Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

7.2 Conditions for safe storage, including any incompatibilities

Keep out of access to unauthorised individuals. Not to be stored in gangways or stair wells. Store product closed and only in original packing. Observe special regulations for aerosols! Observe special storage conditions. Do not store with flammable or self-igniting materials. Keep protected from direct sunlight and temperatures over 50°C. Store in a well-ventilated place. Store cool.

7.3 Specific end use(s)

No information available at present.

Page 5 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.05.2024 / 0004
Replacing version dated / version: 10.02.2023 / 0003
Valid from: 28.05.2024
PDF print date: 28.05.2024
Prüfgas 918/5

Observe the instructions for good working practice and the recommendations for risk assessment.
Consult hazardous substance information systems, e.g. from the professional associations, the chemical industry or different industries,
depending on the application (building materials, wood, chemistry, laboratory, leather, metal).

SECTION 8: Exposure controls/personal protection

8.1 Control parameters

| Chemical Name | Propan-2-ol | | |
|---|--|-----|--|
| WEL-TWA: 400 ppm (999 mg/m ³) | WEL-STEL: 500 ppm (1250 mg/m ³) | --- | |
| Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Alcohol 25/a i-Propanol (81 01 631) - Compur - KITA-122 SA(C) (549 277) - Compur - KITA-150 U (550 382) - DFG (D) (Lösungsmittelgemische), DFG (E) (Solvent mixtures 6) - 2013, 2002 - EU project BC/CEN/ENTR/000/2002-16 card 66-3 (2004) - NIOSH 1400 (ALCOHOLS I) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 - Draeger - Alcohol 100/a (CH 29 701) | | |
| BMGV: --- | Other information: --- | | |
| Chemical Name | Ethyl acetate | | |
| WEL-TWA: 200 ppm (734 mg/m ³) (WEL-TWA, EU) | WEL-STEL: 400 ppm (1468 mg/m ³) (WEL-STEL, EU) | --- | |
| Monitoring procedures: | <ul style="list-style-type: none"> - Draeger - Ethyl Acetate 200/a (CH 20 201) - Compur - KITA-111 SA (549 160) - Compur - KITA-111 U(C) (549 178) - DFG Meth. Nr. 1 (D) (Lösungsmittelgemische 2), DFG (E) (Solvent mixtures 2) - 1993, 2002 - DFG Meth. Nr. 2 (D) (Lösungsmittelgemische 3), DFG (E) (Solvent mixtures 3) - 2014, 2002 - DFG Meth. Nr. 6 (D) (Lösungsmittelgemische 4), DFG (E) (Solvent mixtures 4) - 2014, 2002 - NIOSH 1457 (ETHYL ACETATE) - 1994 - NIOSH 2549 (VOLATILE ORGANIC COMPOUNDS (SCREENING)) - 1996 | | |
| BMGV: --- | Other information: --- | | |
| Chemical Name | Butane | | |
| WEL-TWA: 600 ppm (1450 mg/m ³) | WEL-STEL: 750 ppm (1810 mg/m ³) | --- | |
| Monitoring procedures: | <ul style="list-style-type: none"> - Compur - KITA-221 SA (549 459) - OSHA PV2010 (n-Butane) - 1993 | | |
| BMGV: --- | Other information: --- | | |
| Chemical Name | Propane | | |
| WEL-TWA: 1000 ppm (ACGIH) | WEL-STEL: --- | --- | |
| Monitoring procedures: | <ul style="list-style-type: none"> - Compur - KITA-125 SA (549 954) - OSHA PV2077 (Propane) - 1990 | | |
| BMGV: --- | Other information: --- | | |
| Chemical Name | Isobutane | | |
| WEL-TWA: 1000 ppm (EX) (ACGIH) | WEL-STEL: --- | --- | |
| Monitoring procedures: | <ul style="list-style-type: none"> - Compur - KITA-113 SB(C) (549 368) | | |
| BMGV: --- | Other information: --- | | |

| Propan-2-ol | | | | | | |
|---------------------|--|------------------|------------|-------|------|------|
| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
| | Environment - freshwater | | PNEC | 140,9 | mg/l | |
| | Environment - marine | | PNEC | 140,9 | mg/l | |

Page 6 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.05.2024 / 0004

Replacing version dated / version: 10.02.2023 / 0003

Valid from: 28.05.2024

PDF print date: 28.05.2024

Prüfgas 918/5

| | | | | | | |
|---------------------|--|-----------------------------|------|-------|--------------|--|
| | Environment - sediment, freshwater | | PNEC | 552 | mg/kg dw | |
| | Environment - sediment, marine | | PNEC | 552 | mg/kg dw | |
| | Environment - soil | | PNEC | 28 | mg/kg dw | |
| | Environment - sewage treatment plant | | PNEC | 2251 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 140,9 | mg/l | |
| | Environment - oral (animal feed) | | PNEC | 160 | mg/kg feed | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 319 | mg/kg bw/day | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 89 | mg/m3 | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 26 | mg/kg bw/day | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 888 | mg/kg bw/day | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 500 | mg/m3 | |

Ethyl acetate

| Area of application | Exposure route / Environmental compartment | Effect on health | Descriptor | Value | Unit | Note |
|---------------------|--|------------------------------|------------|-------|-------|------|
| | Environment - freshwater | | PNEC | 0,24 | mg/l | |
| | Environment - marine | | PNEC | 0,024 | mg/l | |
| | Environment - water, sporadic (intermittent) release | | PNEC | 1,65 | mg/l | |
| | Environment - sediment, freshwater | | PNEC | 1,15 | mg/kg | |
| | Environment - sediment, marine | | PNEC | 0,115 | mg/kg | |
| | Environment - soil | | PNEC | 0,148 | mg/kg | |
| | Environment - sewage treatment plant | | PNEC | 650 | mg/l | |
| | Environment - oral (animal feed) | | PNEC | 200 | mg/kg | |
| Consumer | Human - oral | Long term, systemic effects | DNEL | 4,5 | mg/kg | |
| Consumer | Human - dermal | Long term, systemic effects | DNEL | 37 | mg/kg | |
| Consumer | Human - inhalation | Long term, systemic effects | DNEL | 367 | mg/m3 | |
| Consumer | Human - inhalation | Long term, local effects | DNEL | 367 | mg/m3 | |
| Consumer | Human - inhalation | Short term, systemic effects | DNEL | 734 | mg/m3 | |
| Consumer | Human - inhalation | Short term, local effects | DNEL | 734 | mg/m3 | |
| Workers / employees | Human - dermal | Long term, systemic effects | DNEL | 63 | mg/kg | |
| Workers / employees | Human - inhalation | Long term, systemic effects | DNEL | 734 | mg/m3 | |
| Workers / employees | Human - inhalation | Long term, local effects | DNEL | 734 | mg/m3 | |
| Workers / employees | Human - inhalation | Short term, systemic effects | DNEL | 1468 | mg/m3 | |

GB

Page 7 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.05.2024 / 0004
Replacing version dated / version: 10.02.2023 / 0003
Valid from: 28.05.2024
PDF print date: 28.05.2024
Prüfgas 918/5

| | | | | | | |
|---------------------|--------------------|---------------------------|------|------|-------------------|--|
| Workers / employees | Human - inhalation | Short term, local effects | DNEL | 1468 | mg/m ³ | |
|---------------------|--------------------|---------------------------|------|------|-------------------|--|

GB - United Kingdom | WEL-TWA = Workplace Exposure Limit - Long-term exposure limit - 8-hour TWA (= time weighted average) reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/CE, 2017/164/EU). (9) = Respirable fraction (2004/37/CE, 2017/164/EU). (11) = Inhalable fraction (2004/37/CE). (12) = Inhalable fraction. Respirable fraction in those Member States that implement, on the date of the entry into force of this Directive, a biomonitoring system with a biological limit value not exceeding 0,002 mg Cd/g creatinine in urine (2004/37/CE). |
| WEL-STEL = Workplace Exposure Limit - Short-term exposure limit - 15-minute reference period (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(8) = Inhalable fraction (2004/37/EC, 2017/164/EU). (9) = Respirable fraction (2004/37/EC, 2017/164/EU). (10) = Short-term exposure limit value in relation to a reference period of 1 minute (2017/164/EU). |
| BMGV = Biological monitoring guidance value (EH40/2005 Workplace exposure limits (Fourth Edition 2020)).
(EU) = Directive 98/24/EC or 2004/37/EC or SCOEL (Biological Limit Value - BLV, Recommendation from the Scientific Committee on Occupational Exposure Limits (SCOEL)) |
| Other information (EH40/2005 Workplace exposure limits (Fourth Edition 2020)): Sen = Capable of causing occupational asthma. Sk = Can be absorbed through skin. Carc = Capable of causing cancer and/or heritable genetic damage.
(EU) = Directive 91/322/EEC, 98/24/EC, 2000/39/EC, 2004/37/EC, 2006/15/EC, 2009/161/EU, 2017/164/EU or 2019/1831/EU:
(13) = The substance can cause sensitisation of the skin and of the respiratory tract (2004/37/CE), (14) = The substance can cause sensitisation of the skin (2004/37/CE). |

8.2 Exposure controls

8.2.1 Appropriate engineering controls

Ensure good ventilation. This can be achieved by local suction or general air extraction.
If this is insufficient to maintain the concentration under the WEL or AGW values, suitable breathing protection should be worn.
Applies only if maximum permissible exposure values are listed here.
Suitable assessment methods for reviewing the effectiveness of protection measures adopted include metrological and non-metrological investigative techniques.
These are specified by e.g. EN 14042.
EN 14042 "Workplace atmospheres. Guide for the application and use of procedures for the assessment of exposure to chemical and biological agents".

8.2.2 Individual protection measures, such as personal protective equipment

General hygiene measures for the handling of chemicals are applicable.
Wash hands before breaks and at end of work.
Keep away from food, drink and animal feedingstuffs.
Remove contaminated clothing and protective equipment before entering areas in which food is consumed.

Eye/face protection:
Tight fitting protective goggles with side protection (EN 166).

Skin protection - Hand protection:
Chemical resistant protective gloves (EN ISO 374).
If applicable
Protective gloves in butyl rubber (EN ISO 374).
Minimum layer thickness in mm:
0,7
Permeation time (penetration time) in minutes:
> 480
The breakthrough times determined in accordance with EN 16523-1 were not obtained under practical conditions.
The recommended maximum wearing time is 50% of breakthrough time.
Protective hand cream recommended.

Skin protection - Other:
Protective working garments (e.g. safety shoes EN ISO 20345, long-sleeved protective working garments).

Respiratory protection:
If OES or MEL is exceeded.

Page 8 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.05.2024 / 0004
 Replacing version dated / version: 10.02.2023 / 0003
 Valid from: 28.05.2024
 PDF print date: 28.05.2024
 Prüfgas 918/5

Gas mask filter AX (EN 14387), code colour brown.
 Observe wearing time limitations for respiratory protection equipment.

Thermal hazards:
 Not applicable

Additional information on hand protection - No tests have been performed.
 In the case of mixtures, the selection has been made according to the knowledge available and the information about the contents.
 Selection of materials derived from glove manufacturer's indications.
 Final selection of glove material must be made taking the breakthrough times, permeation rates and degradation into account.
 Selection of a suitable glove depends not only on the material but also on other quality characteristics and varies from manufacturer to manufacturer.
 In the case of mixtures, the resistance of glove materials cannot be predicted and must therefore be tested before use.
 The exact breakthrough time of the glove material can be requested from the protective glove manufacturer and must be observed.

8.2.3 Environmental exposure controls

No information available at present.

SECTION 9: Physical and chemical properties

9.1 Information on basic physical and chemical properties

| | |
|---|--|
| Physical state: | Aerosol. Active substance: liquid. |
| Colour: | Clear |
| Odour: | Characteristic |
| Melting point/freezing point: | There is no information available on this parameter. |
| Boiling point or initial boiling point and boiling range: | -42 °C (Propane) |
| Flammability: | Does not apply to aerosols. |
| Lower explosion limit: | There is no information available on this parameter. |
| Upper explosion limit: | There is no information available on this parameter. |
| Flash point: | -104 °C (Propane) |
| Auto-ignition temperature: | 400 °C (Propellant gas) |
| Decomposition temperature: | There is no information available on this parameter. |
| pH: | There is no information available on this parameter. |
| Kinematic viscosity: | Does not apply to aerosols. |
| Solubility: | partially |
| Partition coefficient n-octanol/water (log value): | Does not apply to mixtures. |
| Vapour pressure: | 3000 - 3800 hPa (20°C) |
| Density and/or relative density: | 0,5713 g/cm ³ |
| Relative vapour density: | Does not apply to aerosols. |
| Particle characteristics: | Does not apply to aerosols. |

9.2 Other information

| | |
|--------------------|---|
| Explosives: | Product is not explosive. When using: development of explosive vapour/air mixture possible. |
| Oxidising liquids: | No |

SECTION 10: Stability and reactivity

10.1 Reactivity

The product has not been tested.

10.2 Chemical stability

Stable with proper storage and handling.

10.3 Possibility of hazardous reactions

No dangerous reactions are known.

10.4 Conditions to avoid

Heating, open flame, ignition sources
 Pressure increase will result in danger of bursting.

10.5 Incompatible materials

Avoid contact with strong oxidizing agents.

Page 9 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.05.2024 / 0004

Replacing version dated / version: 10.02.2023 / 0003

Valid from: 28.05.2024

PDF print date: 28.05.2024

Prüfgas 918/5

10.6 Hazardous decomposition products

No decomposition when used as directed.

SECTION 11: Toxicological information

11.1. Information on hazard classes as defined in Regulation (EC) No 1272/2008

Possibly more information on health effects, see Section 2.1 (classification).

Prüfgas 918/5

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|-------|------|----------|-------------|--------|
| Acute toxicity, by oral route: | | | | | | n.d.a. |
| Acute toxicity, by dermal route: | | | | | | n.d.a. |
| Acute toxicity, by inhalation: | | | | | | n.d.a. |
| Skin corrosion/irritation: | | | | | | n.d.a. |
| Serious eye damage/irritation: | | | | | | n.d.a. |
| Respiratory or skin sensitisation: | | | | | | n.d.a. |
| Germ cell mutagenicity: | | | | | | n.d.a. |
| Carcinogenicity: | | | | | | n.d.a. |
| Reproductive toxicity: | | | | | | n.d.a. |
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | n.d.a. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | n.d.a. |
| Aspiration hazard: | | | | | | n.d.a. |
| Symptoms: | | | | | | n.d.a. |

Propan-2-ol

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|------------------------------------|----------|-------------|---------|------------------------|---|-------------------|
| Acute toxicity, by oral route: | LD50 | 4570-5840 | mg/kg | Rat | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | 12800-13900 | mg/kg | Rabbit | OECD 402 (Acute Dermal Toxicity) | |
| Acute toxicity, by inhalation: | LC50 | > 25 | mg/l/6h | Rat | OECD 403 (Acute Inhalation Toxicity) | Vapours |
| Acute toxicity, by inhalation: | LC50 | 46600 | mg/l/4h | Rat | | Aerosol |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Irrit. 2 |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mouse | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 476 (In Vitro Mammalian Cell Gene Mutation Test) | Negative |
| Carcinogenicity: | | | | | | Negative |

Page 10 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.05.2024 / 0004
 Replacing version dated / version: 10.02.2023 / 0003
 Valid from: 28.05.2024
 PDF print date: 28.05.2024
 Prüfgas 918/5

| | | | | | | |
|---|-------|------|-------|-----|--|---|
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | STOT SE 3, H336, May cause drowsiness or dizziness. |
| Specific target organ toxicity - repeated exposure (STOT-RE): | | | | | | Target organ(s): liver |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 900 | mg/kg | Rat | OECD 408 (Repeated Dose 90-Day Oral Toxicity Study in Rodents) | |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 5000 | ppm | Rat | | Vapours (OECD 451) |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | breathing difficulties, unconsciousness, vomiting, headaches, fatigue, dizziness, nausea, eyes, reddened, watering eyes |

| Ethyl acetate | | | | | | |
|------------------------------------|----------|--------|---------|------------------------|--|---|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by oral route: | LD50 | 4934 | mg/kg | Rabbit | OECD 401 (Acute Oral Toxicity) | |
| Acute toxicity, by dermal route: | LD50 | >20000 | mg/kg | Rabbit | | |
| Acute toxicity, by inhalation: | LC0 | 29,3 | mg/l/4h | Rat | | Vapours |
| Skin corrosion/irritation: | | | | Rabbit | OECD 404 (Acute Dermal Irritation/Corrosion) | Not irritant, Repeated exposure may cause skin dryness or cracking. |
| Serious eye damage/irritation: | | | | Rabbit | OECD 405 (Acute Eye Irritation/Corrosion) | Eye Irrit. 2 |
| Respiratory or skin sensitisation: | | | | Guinea pig | OECD 406 (Skin Sensitisation) | No (skin contact) |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | Mammalian | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Mammalian | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |
| Carcinogenicity: | | | | | | Negative |
| Reproductive toxicity: | | | | | | Negative |

GB

Page 11 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.05.2024 / 0004
Replacing version dated / version: 10.02.2023 / 0003
Valid from: 28.05.2024
PDF print date: 28.05.2024
Prüfgas 918/5

| | | | | | | |
|---|-------|-------|------------|-----|---|---|
| Specific target organ toxicity - single exposure (STOT-SE): | | | | | | STOT SE 3, H336, May cause drowsiness or dizziness. |
| Specific target organ toxicity - repeated exposure (STOT-RE), oral: | NOAEL | 900 | mg/kg bw/d | Rat | Regulation (EC) 440/2008 B.26 (SUB-CHRONIC ORAL TOXICITY TEST REPEATED DOSE 90 - DAY (RODENTS)) | |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 0,002 | mg/kg | Rat | Regulation (EC) 440/2008 B.29 (SUB-CHRONIC INHALATION TOXICITY STUDY 90-DAY REPEATED (RODENTS)) | |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | lack of appetite, breathing difficulties, drowsiness, unconsciousness, drop in blood pressure, cornea opacity, coughing, headaches, gastrointestinal disturbances, intoxication, drowsiness, mucous membrane irritation, dizziness, salivation, nausea and vomiting., fatigue |

| Butane | | | | | | |
|--------------------------------|----------|-------|---------|------------------------|--|----------|
| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Human being | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Rat | OECD 474 (Mammalian Erythrocyte Micronucleus Test) | Negative |

Page 12 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.05.2024 / 0004
 Replacing version dated / version: 10.02.2023 / 0003
 Valid from: 28.05.2024
 PDF print date: 28.05.2024
 Prüfgas 918/5

| | | | | | | |
|---|-------|--------|------|-----|---|--|
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEC | 21,394 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test) | |
| Aspiration hazard: | | | | | | No |
| Symptoms: | | | | | | ataxia, breathing difficulties, drowsiness, unconsciousness, frostbite, disturbed heart rhythm, headaches, cramps, intoxication, dizziness, nausea and vomiting. |

Propane

| Toxicity / effect | Endpoint | Value | Unit | Organism | Test method | Notes |
|---|----------|--------|---------|------------------------|---|------------------------------------|
| Acute toxicity, by inhalation: | LC50 | 658 | mg/l/4h | Rat | | |
| Acute toxicity, by inhalation: | LC50 | 260000 | ppmV/4h | Rat | | Gasses, Male, Analogous conclusion |
| Skin corrosion/irritation: | | | | | | Not irritant |
| Serious eye damage/irritation: | | | | | | Not irritant |
| Germ cell mutagenicity: | | | | | OECD 473 (In Vitro Mammalian Chromosome Aberration Test) | Negative |
| Germ cell mutagenicity: | | | | Salmonella typhimurium | OECD 471 (Bacterial Reverse Mutation Test) | Negative |
| Reproductive toxicity (Developmental toxicity): | NOAEC | 21,641 | mg/l | | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test) | |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | NOAEL | 7,214 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test) | |
| Specific target organ toxicity - repeated exposure (STOT-RE), inhalat.: | LOAEL | 21,641 | mg/l | Rat | OECD 422 (Combined Repeated Dose Tox. Study with the Reproduction/Development. Tox. Screening Test) | |
| Aspiration hazard: | | | | | | No |

Page 14 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.05.2024 / 0004
 Replacing version dated / version: 10.02.2023 / 0003
 Valid from: 28.05.2024
 PDF print date: 28.05.2024
 Prüfgas 918/5

| | | | | | | | |
|--|--|--|--|--|--|--|---|
| 12.2. Persistence and degradability: | | | | | | | n.d.a. |
| 12.3. Bioaccumulative potential: | | | | | | | n.d.a. |
| 12.4. Mobility in soil: | | | | | | | n.d.a. |
| 12.5. Results of PBT and vPvB assessment | | | | | | | n.d.a. |
| 12.6. Endocrine disrupting properties: | | | | | | | Does not apply to mixtures. |
| 12.7. Other adverse effects: | | | | | | | No information available on other adverse effects on the environment. |

| Propan-2-ol | | | | | | | |
|--|----------|------|-------|------|-------------------------|--|-------------------------------------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | >100 | mg/l | Leuciscus idus | | |
| 12.1. Toxicity to fish: | LC50 | 96h | 1400 | mg/l | Lepomis macrochirus | | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 2285 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to daphnia: | EC50 | 16d | 141 | mg/l | Daphnia magna | | |
| 12.1. Toxicity to algae: | EC50 | 72h | >100 | mg/l | Desmodesmus subspicatus | | |
| 12.2. Persistence and degradability: | | 21d | 95 | % | | OECD 301 E (Ready Biodegradability - Modified OECD Screening Test) | Readily biodegradable |
| 12.2. Persistence and degradability: | | | 99,9 | % | | OECD 303 A (Simulation Test - Aerobic Sewage Treatment - Activated Sludge Units) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | Log Pow | | 0,05 | | | OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method) | Slight |
| 12.3. Bioaccumulative potential: | BCF | | 3,2 | | | | Low |
| 12.4. Mobility in soil: | Koc | | 1,1 | | | | Expert judgement |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC50 | | >1000 | mg/l | activated sludge | | |
| Other organisms: | IC50 | 3d | 2104 | mg/l | Lactuca sativa | | |
| Other information: | ThOD | | 2,4 | g/g | | | |
| Other information: | BOD5 | | 53 | % | | | |
| Other information: | COD | | 96 | % | | | References |
| Other information: | COD | | 2,4 | g/g | | | |
| Other information: | BOD | | 1171 | mg/g | | | |

| Ethyl acetate | | | | | | | |
|-------------------------|-----------|------|-------|------|---------------------|-------------|-------|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | NOEC/NOEL | 32d | <9,65 | mg/l | Pimephales promelas | | |

Page 15 of 20

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II

Revision date / version: 28.05.2024 / 0004

Replacing version dated / version: 10.02.2023 / 0003

Valid from: 28.05.2024

PDF print date: 28.05.2024

Prüfgas 918/5

| | | | | | | | |
|--|-----------|-------|---------|------------|---------------------------------|---|--|
| 12.1. Toxicity to fish: | LC50 | 96h | 230 | mg/l | Pimephales promelas | | |
| 12.1. Toxicity to fish: | LC50 | 48h | 333 | mg/l | Leuciscus idus | | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 610 | mg/l | Daphnia magna | DIN 38412 T.11 | |
| 12.1. Toxicity to daphnia: | NOEC/NOEL | 21d | 2,4 | mg/l | Daphnia magna | OECD 211 (Daphnia magna Reproduction Test) | |
| 12.1. Toxicity to daphnia: | EC50 | 48h | 165 | mg/l | | | Daphnia cucullata |
| 12.1. Toxicity to algae: | EC50 | 48h | 5600 | mg/l | Desmodesmus subspicatus | DIN 38412 T.9 | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 96h | 2000 | mg/l | Scenedesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | EC50 | 96h | >2000 | mg/l | Pseudokirchneriella subcapitata | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | NOEC/NOEL | 72h | >100 | mg/l | Desmodesmus subspicatus | OECD 201 (Alga, Growth Inhibition Test) | |
| 12.1. Toxicity to algae: | EC50 | 48h | 3300 | mg/l | Scenedesmus subspicatus | | |
| 12.2. Persistence and degradability: | | 20d | 79 | % | | OECD 301 D (Ready Biodegradability - Closed Bottle Test) | Readily biodegradable |
| 12.3. Bioaccumulative potential: | BCF | 72h | 30 | | | | (Fish) |
| 12.3. Bioaccumulative potential: | Log Kow | | 0,68 | | | OECD 107 (Partition Coefficient (n-octanol/water) - Shake Flask Method) | Bioaccumulation is unlikely (LogPow < 1).25 °C |
| 12.4. Mobility in soil: | H (Henry) | | 0,00012 | atm*m3/mol | | | |
| 12.4. Mobility in soil: | Koc | | 3 | | | | |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |
| Toxicity to bacteria: | EC10 | 16h | 2900 | mg/l | Escherichia coli | | |
| Toxicity to bacteria: | EC50 | 15min | 5870 | mg/l | Photobacterium phosphoreum | | |
| Toxicity to bacteria: | EC10 | 18h | 2900 | mg/l | Pseudomonas putida | DIN 38412 T.8 | |

Butane

| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
|----------------------------------|----------|------|-------|------|----------|-------------|---|
| 12.1. Toxicity to fish: | LC50 | 96h | 24,11 | mg/l | | QSAR | |
| 12.1. Toxicity to daphnia: | LC50 | 48h | 14,22 | mg/l | | QSAR | |
| 12.3. Bioaccumulative potential: | Log Pow | | 2,98 | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |

GB

Page 16 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.05.2024 / 0004
Replacing version dated / version: 10.02.2023 / 0003
Valid from: 28.05.2024
PDF print date: 28.05.2024
Prüfgas 918/5

| | | | | | | | |
|--|--|--|--|--|--|--|-------------------------------------|
| 12.4. Mobility in soil: | | | | | | | Not to be expected |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Propane | | | | | | | |
|--|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.3. Bioaccumulative potential: | Log Pow | | 2,28 | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

| Isobutane | | | | | | | |
|--|----------|------|-------|------|----------|-------------|---|
| Toxicity / effect | Endpoint | Time | Value | Unit | Organism | Test method | Notes |
| 12.1. Toxicity to fish: | LC50 | 96h | 27,98 | mg/l | | | |
| 12.1. Toxicity to algae: | EC50 | 96h | 7,71 | mg/l | | | |
| 12.2. Persistence and degradability: | | | | | | | Readily biodegradable |
| 12.3. Bioaccumulative potential: | | | | | | | A notable biological accumulation potential is not to be expected (LogPow 1-3). |
| 12.5. Results of PBT and vPvB assessment | | | | | | | No PBT substance, No vPvB substance |

SECTION 13: Disposal considerations

13.1 Waste treatment methods

For the substance / mixture / residual amounts

EC disposal code no.:

The waste codes are recommendations based on the scheduled use of this product. Owing to the user's specific conditions for use and disposal, other waste codes may be allocated under certain circumstances. (2014/955/EU)

16 05 04 gases in pressure containers (including halons) containing hazardous substances

Recommendation:

Sewage disposal shall be discouraged.

Pay attention to local and national official regulations.

Take full aerosol cans to problem waste collection.

Take emptied aerosol cans to valuable material collection.

For contaminated packing material

Pay attention to local and national official regulations.

Recommendation:

Do not perforate, cut up or weld uncleaned container.

Recycling

15 01 04 metallic packaging

SECTION 14: Transport information

General statements

Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.05.2024 / 0004
Replacing version dated / version: 10.02.2023 / 0003
Valid from: 28.05.2024
PDF print date: 28.05.2024
Prüfgas 918/5

Transport by road/by rail (ADR/RID)

14.1. UN number or ID number: 1950
14.2. UN proper shipping name:
UN 1950 AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
14.5. Environmental hazards: Not applicable
Tunnel restriction code: D
Classification code: 5F
LQ: 1 L
Transport category: 2



Transport by sea (IMDG-code)

14.1. UN number or ID number: 1950
14.2. UN proper shipping name:
UN 1950 AEROSOLS
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
14.5. Environmental hazards: Not applicable
Marine Pollutant: Not applicable
EmS: F-D, S-U



Transport by air (IATA)

14.1. UN number or ID number: 1950
14.2. UN proper shipping name:
UN 1950 Aerosols, flammable
14.3. Transport hazard class(es): 2.1
14.4. Packing group: -
14.5. Environmental hazards: Not applicable



14.6. Special precautions for user

Persons employed in transporting dangerous goods must be trained.
All persons involved in transporting must observe safety regulations.
Precautions must be taken to prevent damage.

14.7. Maritime transport in bulk according to IMO instruments

Freighted as packaged goods rather than in bulk, therefore not applicable.
Minimum amount regulations have not been taken into account.
Danger code and packing code on request.
Comply with special provisions.

SECTION 15: Regulatory information

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture

Observe restrictions:
Comply with national regulations/laws governing the protection of young people at work (national implementation of the Directive 94/33/EC)!
Comply with trade association/occupational health regulations.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 1 - The following categories apply to this product (others may also need to be considered according to storage, handling etc.):

| Hazard categories | Notes to Annex I | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) of dangerous substances as referred to in Article 3(10) for the application of - Upper-tier requirements |
|-------------------|------------------|---|---|
| P3a | 11.1 | 150 (netto) | 500 (netto) |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2012/18/EU ("Seveso III"), Annex I, Part 2 - This product contains the substances listed below:

Page 18 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.05.2024 / 0004
 Replacing version dated / version: 10.02.2023 / 0003
 Valid from: 28.05.2024
 PDF print date: 28.05.2024
 Prüfgas 918/5

| Entry Nr | Dangerous substances | Notes to Annex I | Qualifying quantity (tonnes) for the application of - Lower-tier requirements | Qualifying quantity (tonnes) for the application of - Upper-tier requirements |
|----------|--|------------------|---|---|
| 18 | Liquefied flammable gases, Category 1 or 2 (including LPG) and natural gas | 19 | 50 | 200 |

The Notes to Annex 1 of Directive 2012/18/EU, in particular those named in the tables here and notes 1-6, must be taken into account when assigning categories and qualifying quantities.

Directive 2010/75/EU (VOC): 99,96 %

Observe incident regulations.

National requirements/regulations on safety and health protection must be applied when using work equipment.

15.2 Chemical safety assessment

A chemical safety assessment is not provided for mixtures.

SECTION 16: Other information

Revised sections: 3, 8
 Employee training in handling dangerous goods is required.
 These details refer to the product as it is delivered.
 Employee instruction/training in handling hazardous materials is required.

Classification and processes used to derive the classification of the mixture in accordance with the ordinance (EG) 1272/2008 (CLP):

| Classification in accordance with regulation (EC) No. 1272/2008 (CLP) | Evaluation method used |
|---|---|
| Aerosol 1, H222 | Classification according to calculation procedure. |
| Aerosol 1, H229 | Classification based on the form or physical state. |

The following phrases represent the posted Hazard Class and Risk Category Code (GHS/CLP) of the product and the constituents.
 H225 Highly flammable liquid and vapour.
 H319 Causes serious eye irritation.
 H336 May cause drowsiness or dizziness.
 EUH066 Repeated exposure may cause skin dryness or cracking.

Aerosol — Aerosols
 Flam. Liq. — Flammable liquid
 Eye Irrit. — Eye irritation
 STOT SE — Specific target organ toxicity - single exposure - narcotic effects

Key literature references and sources for data:

Regulation (EC) No 1907/2006 (REACH) and Regulation (EC) No 1272/2008 (CLP) as amended.
 Guidelines for the preparation of safety data sheets as amended (ECHA).
 Guidelines on labelling and packaging according to the Regulation (EG) Nr. 1272/2008 (CLP) as amended (ECHA).
 Safety data sheets for the constituent substances.
 ECHA Homepage - Information about chemicals.
 GESTIS Substance Database (Germany).
 German Environment Agency "Rigoletto" information site on substances that are hazardous to water (Germany).
 EU Occupation Exposure Limits Directives 91/322/EEC, 2000/39/EC, 2006/15/EC, 2009/161/EU, (EU) 2017/164, (EU) 2019/1831, each as amended.
 National Lists of Occupational Exposure Limits for each country as amended.
 Regulations on the transport of hazardous goods by road, rail, sea and air (ADR, RID, IMDG, IATA) as amended.

Page 19 of 20
 Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
 Revision date / version: 28.05.2024 / 0004
 Replacing version dated / version: 10.02.2023 / 0003
 Valid from: 28.05.2024
 PDF print date: 28.05.2024
 Prüfgas 918/5

Any abbreviations and acronyms used in this document:

acc., acc. to according, according to
 ADR Accord européen relatif au transport international des marchandises Dangereuses par Route (= European Agreement concerning the International Carriage of Dangerous Goods by Road)
 AOX Adsorbable organic halogen compounds
 approx. approximately
 Art., Art. no. Article number
 ASTM ASTM International (American Society for Testing and Materials)
 ATE Acute Toxicity Estimate
 BAM Bundesanstalt für Materialforschung und -prüfung (= Federal Institute for Materials Research and Testing, Germany)
 BAuA Bundesanstalt für Arbeitsschutz und Arbeitsmedizin (= Federal Institute for Occupational Health and Safety, Germany)
 BCF Bioconcentration factor
 BSEF The International Bromine Council
 CAS Chemical Abstracts Service
 CLP Classification, Labelling and Packaging (REGULATION (EC) No 1272/2008 on classification, labelling and packaging of substances and mixtures)
 CMR carcinogenic, mutagenic, reproductive toxic
 DMEL Derived Minimum Effect Level
 DNEL Derived No Effect Level
 DOC Dissolved organic carbon
 e.g. for example (abbreviation of Latin 'exempli gratia'), for instance
 EbCx, EyCx, EbLx (x = 10, 50) Effect Concentration/Level of x % on reduction of the biomass (algae, plants)
 EC European Community
 ECHA European Chemicals Agency
 ECx, ELx (x = 0, 3, 5, 10, 20, 50, 80, 100) Effect Concentration/Level for x % effect
 EEC European Economic Community
 EINECS European Inventory of Existing Commercial Chemical Substances
 ELINCS European List of Notified Chemical Substances
 EN European Norms
 EPA United States Environmental Protection Agency (United States of America)
 ErCx, EμCx, ErLx (x = 10, 50) Effect Concentration/Level of x % on inhibition of the growth rate (algae, plants)
 etc. et cetera
 EU European Union
 EVAL Ethylene-vinyl alcohol copolymer
 Fax. Fax number
 gen. general
 GHS Globally Harmonized System of Classification and Labelling of Chemicals
 GWP Global warming potential
 Koc Adsorption coefficient of organic carbon in the soil
 Kow octanol-water partition coefficient
 IARC International Agency for Research on Cancer
 IATA International Air Transport Association
 IBC (Code) International Bulk Chemical (Code)
 IMDG-code International Maritime Code for Dangerous Goods
 incl. including, inclusive
 IUCLID International Uniform Chemical Information Database
 IUPAC International Union for Pure Applied Chemistry
 LC50 Lethal Concentration to 50 % of a test population
 LD50 Lethal Dose to 50% of a test population (Median Lethal Dose)
 Log Koc Logarithm of adsorption coefficient of organic carbon in the soil
 Log Kow, Log Pow Logarithm of octanol-water partition coefficient
 LQ Limited Quantities
 MARPOL International Convention for the Prevention of Marine Pollution from Ships
 mg/kg bw mg/kg body weight
 mg/kg bw/d, mg/kg bw/day mg/kg body weight/day
 mg/kg dw mg/kg dry weight
 mg/kg wwt mg/kg wet weight
 n.a. not applicable

GB

Page 20 of 20
Safety data sheet according to Regulation (EC) No 1907/2006, Annex II
Revision date / version: 28.05.2024 / 0004
Replacing version dated / version: 10.02.2023 / 0003
Valid from: 28.05.2024
PDF print date: 28.05.2024
Prüfgas 918/5

n.av. not available
n.c. not checked
n.d.a. no data available
NIOSH National Institute for Occupational Safety and Health (USA)
NLP No-longer-Polymer
NOEC, NOEL No Observed Effect Concentration/Level
OECD Organisation for Economic Co-operation and Development
org. organic
OSHA Occupational Safety and Health Administration (USA)
PBT persistent, bioaccumulative and toxic
PE Polyethylene
PNEC Predicted No Effect Concentration
ppm parts per million
PVC Polyvinylchloride
REACH Registration, Evaluation, Authorisation and Restriction of Chemicals (REGULATION (EC) No 1907/2006 concerning the Registration, Evaluation, Authorisation and Restriction of Chemicals)
REACH-IT List-No. 6/7/8/9xx-xxx-x No. is automatically assigned, e.g. to pre-registrations without a CAS No. or other numerical identifier. List Numbers do not have any legal significance, rather they are purely technical identifiers for processing a submission via REACH-IT.
RID Règlement concernant le transport International ferroviaire de marchandises Dangereuses (= Regulation concerning the International Carriage of Dangerous Goods by Rail)
SVHC Substances of Very High Concern
Tel. Telephone
TOC Total organic carbon
UN RTDG United Nations Recommendations on the Transport of Dangerous Goods
VOC Volatile organic compounds
vPvB very persistent and very bioaccumulative

The statements made here should describe the product with regard to the necessary safety precautions - they are not meant to guarantee definite characteristics - but they are based on our present up-to-date knowledge.
No responsibility.

These statements were made by:

Chemical Check GmbH, Chemical Check Platz 1-7, D-32839 Steinheim, Tel.: +49 5233 94 17 0, Fax: +49 5233 94 17 90

© by Chemical Check GmbH Gefahrstoffberatung. The copying or changing of this document is forbidden except with consent of the Chemical Check GmbH Gefahrstoffberatung.